

Completely pre-assembled Signal Towers / ClearSIGN

Buzzer module BM Contin. tone 24VDC

Part No.:	656.000.55
Series:	ClearSIGN

**MECHANICAL DATA**

Height	19 mm
Diameter	85 mm
Materials	PC/ABS
Housing colour	Black
Protection category	IP66
Connection	Cable
cross-sectional area minimum	0,14mm ² / 26AWG
cross-sectional area maximum	0,50mm ² / 20AWG
Cable entry	Membrane grommet
Cable entry minimum	d = 1 mm
Cable entry maximum	d = 9 mm
Type of fixing	Base mounting
Acoustic service life	5,000 h minimum
Working temperature minimum	-20°C
Working temperature maximum	+50°C
Weight with packaging	56 g
Product weight	30 g

ELECTRICAL DATA

Operating voltage	24V
Operating voltage type	DC
Operating voltage tolerance	+/- 10%
Rated operational voltage	24 VDC
Rated operational current	40 mA
Rated inrush current	500 mA
Protection class	Protection class 2
Pollution degree	3

ACUSTICAL DATA

Volume/dB(max) at 1m distance	85,0 dB (A)
Acoustic signal image	Continuous tone
Audio frequency	4400 Hz



For additional installation and mounting information, refer to the appropriate user guide at www.werma.com. This printed copy is for information only and is subject to alteration.