

KombiSIGN 71 / LED Revolving Signal Beacon 644  
**LED Rotating light el. 24VAC/DC GN**



|           |              |
|-----------|--------------|
| Part No.: | 644.230.75   |
| Series:   | KombiSIGN 71 |

**MECHANICAL DATA**

|                             |                   |
|-----------------------------|-------------------|
| Height                      | 66 mm             |
| Diameter                    | 70 mm             |
| Materials                   | PC                |
| Dome colour                 | Green             |
| Protection category         | IP65              |
| Service life optical        | 100,000 h maximum |
| Working temperature minimum | -20°C             |
| Working temperature maximum | +50°C             |
| UL Type Rating              | Type 12           |
| Weight with packaging       | 84 g              |
| Product weight              | 69 g              |

**ELECTRICAL DATA**

|                             |                    |
|-----------------------------|--------------------|
| Operating voltage           | 24V                |
| Operating voltage type      | AC/DC              |
| Operating voltage frequency | 50Hz               |
| Operating voltage tolerance | +/- 10%            |
| Rated operational voltage   | 24 VDC             |
| Rated operational current   | 40 mA              |
| Rated inrush current        | 500 mA             |
| Protection class            | Protection class 2 |
| Pollution degree            | 3                  |

**OPTICAL DATA**

|                          |           |
|--------------------------|-----------|
| Light source             | LED       |
| Light colour             | Green     |
| Optical signal image     | Revolving |
| Rotation frequency (rpm) | 120 U/min |



For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.

KombiSIGN 71 / LED Revolving Signal Beacon 644

**LED Rotating light el. 24VAC/DC GN**

**DRAWING**



For additional installation and mounting information, refer to the appropriate user guide at [www.werma.com](http://www.werma.com). This printed copy is for information only and is subject to alteration.