

# Series C3200

• Cable • Hose • Rope • Wire

**To handle 1/2" through 1" O.D.  
For storage only. No live connections.**

- A 4-1/2" x 9" (114mm x 229mm) opening in the drum to initiate winding.
- Designed for storage of long lengths of cable, hose, rope, wire or other materials.
- Choose disc rewind or removable direct crank rewind.
- Supplied with spring actuated pin lock.
- Optional divider discs can be placed at almost any point. Be sure to specify spacing of discs on your order.
- Rollers and roller mounting brackets are accessory items. Specify roller position.
- For power rewind, see Series C on page 3.



Standard configuration with crank handle shown



**Optional Aluminum Hand Cart**  
4300-AL mounting available.

**PARTS DRAWING – ISO 117**

| Model Number | Cable Capacity of Reel<br>feet m |           |           |         | Approx. Weight<br>Crank Rewind<br>lb. kg |      | Reel Dimensions***<br>In. mm |      |            |            |       |      |      |
|--------------|----------------------------------|-----------|-----------|---------|--|------|------------------------------|------|------------|------------|-------|------|------|
|              | O.D. In.<br>mm                   | 1/2<br>13 | 3/4<br>19 | 1<br>25 | NET                                      | SHIP | A                            | B    | E<br>CRANK | F<br>CRANK | G     | H    | X    |
| C3216-25-26  | -                                | 350       | 150       |         | 81                                       | 123  | 13                           | 7.5  | 24.75      | 20.75      | 27.88 | 15.5 | 7.75 |
|              | -                                | 107       | 46        |         | 37                                       | 56   | 330                          | 191  | 629        | 527        | 708   | 394  | 197  |
| C3218-25-26  | 1000                             | 450       | 200       |         | 85                                       | 127  | 15                           | 9.5  | 24.75      | 22.75      | 27.88 | 15.5 | 7    |
|              | 305                              | 137       | 61        |         | 39                                       | 58   | 381                          | 241  | 629        | 578        | 708   | 394  | 178  |
| C3222-25-26  | -                                | 700       | 300       |         | 93                                       | 135  | 19                           | 13.5 | 24.75      | 26.75      | 27.88 | 15.5 | 11   |
|              | -                                | 213       | 91        |         | 42                                       | 61   | 483                          | 343  | 629        | 679        | 708   | 394  | 279  |
| C3228-25-26  | -                                | 1000      | 500       |         | 109                                      | 151  | 25.5                         | 20   | 24.75      | 33.25      | 27.88 | 15.5 | 17.5 |
|              | -                                | 305       | 152       |         | 49                                       | 68   | 648                          | 508  | 629        | 845        | 708   | 394  | 445  |
| C3230-25-26  | -                                | -         | 500       |         | 113                                      | 155  | 27.5                         | 22   | 24.75      | 35.25      | 27.88 | 15.5 | 19.5 |
|              | -                                | -         | 152       |         | 51                                       | 70   | 689                          | 559  | 629        | 895        | 708   | 394  | 495  |
| C3234-25-26  | -                                | 1300      | 650       |         | 122                                      | 164  | 31.5                         | 26   | 24.75      | 39.25      | 27.88 | 15.5 | 23.5 |
|              | -                                | 396       | 198       |         | 55                                       | 74   | 800                          | 660  | 629        | 997        | 708   | 394  | 597  |

**Notes:**

1. Specifications subject to change.
2. Upon request, reels can be supplied with drum lengths other than shown and with disc sizes in other diameters.
3. Dimensions reflect pressed frames.
4. Requires 3-1/2" clearance to remove crank handle.
5. Subtract 5" from "F" dimension for disc rewind.
6. Be sure to check dimensions and weights prior to ordering.

\*\*\* X, Y indicate mounting holes. See page 2.

