

**To handle 3/4" through 1" O.D. cable.
For storage only. No live connections.**

- Heavy-duty reels.
- 4-1/2" x 9" (114 mm x 229 mm) opening in the drum.
- Many optional configurations available.
- Gear-driven crank rewind; or chain and sprocket drive powered by electric, compressed air or hydraulic motor.
- Auxiliary crank rewind is available on power reels.
- Crank rewind reels supplied with pinion brake.
- Power rewind standard with a comet brake.
- Consult factory for other brakes and locking devices.
- Rollers and roller mounting brackets are accessory items. Specify roller position.
- Divider discs available. Specify spacing.
- Drum diameters other than the standard are available.
Note: Larger drum diameter reduces reel capacity.



Standard configuration shown

PARTS DRAWING – ISO 71

Model Number <small>For power rewind see Note 5</small>	Cable Capacity of Reel feet m			Approx. Weight Crank Rewind lb. kg		Reel Dimensions*** in. mm									
	3/4 19	1 25		NET	SHIP	A	B	D	E	F CRANK	F POWER	G	H	X	Y
C20-19-21	250	150		66	101	17	11.5	20.5	18.75	20	24.5	21.5	12.12	9	16.75
	76	46		30	46	432	292	521	476	508	622	546	308	229	425
C26-19-21	350	200		78	113	23	17.5	20.5	18.75	26	30.5	21.5	12.12	15	16.75
	107	61		35	51	584	445	521	476	660	775	546	308	381	425
C20-23-24	-	250		73	108	17	11.5	20.5	22.75	20	24.5	23.5	12.12	9	16.75
	-	76		33	49	432	292	521	578	508	622	597	308	229	425
C28-23-24	-	475		89	124	25.5	20	20.5	22.75	28.5	33	23.5	12.12	17.5	16.75
	-	145		40	56	648	508	521	578	724	838	597	308	445	425
C20-25-26	-	325		86	121	17	11.5	25.5	24.75	20	24.5	27.88	15.5	9	21.75
	-	99		39	55	432	292	648	629	508	622	708	394	229	552
C24-25-26	-	450		94	129	21	15.5	25.5	24.75	24	28.5	27.88	15.5	13	21.75
	-	137		43	59	533	394	648	629	610	724	708	394	330	552
C18-30-31	-	375		90	125	15	9.5	25.5	28.75	18	22.5	29.88	15.5	7	21.75
	-	114		41	57	381	241	648	730	457	572	759	394	178	552

Notes:

1. Specifications subject to change.
2. Upon request, reels can be supplied with drum lengths other than shown and with disc sizes in other diameters.
3. Dimensions reflect pressed frames.
4. Weights shown in chart are for crank rewind models. ADD these amounts for power rewind models:

	Net lbs./kg	Ship lbs./kg
Electric	40/18.1	46/20.9
Hydraulic	20/9.1	29/13.2
Air	20/9.1	26/11.8

5. When ordering power rewind models, prefix model number with:

- A** = Air Rewind - Supplied with control valve and 18" air hose.
- EP** = Electric Rewind - (1/2 HP) 12v and 24v DC rewind reels are supplied with switch and solenoid 115v AC rewind reels are not supplied with switch but can be ordered separately.
- HD** = Hydraulic Rewind - Not supplied with control valve.

6. Be sure to check dimensions and weights prior to ordering.

*** X, Y indicate mounting holes. See page 2.

