

Series 3500

- Fuel Dispensing (Consult Factory) • Bulk Transfer
- Fire Protection

To handle 1" through 1-3/4" I.D. hose.

- Economical manual rewind reels for long lengths of hose.
- Choose disc rewind or removable direct crank rewind.
- Supplied with spring actuated pin lock.
- Standard inlet: 90° ball bearing swivel joint, 1-1/2" female NPT threads, and 2" Victaulic® groove.
- Standard outlet: flanged riser with 1-1/2" female NPT threads.
- Standard: inlet, outlet riser, and hub assembly are steel. Options: also available in aluminum or stainless steel.
- Standard pressures to 600 psi (41 bar), available up to 1000 psi (69 bar) – must specify.
- Temperatures from -25°F to +250°F (-32°C to +121°C).
- Rollers and roller mounting brackets are accessory items. Specify roller position.



Standard configuration shown



Optional Aluminum Hand Cart

4300-AL mounting available.

PARTS DRAWING – ISO 111

Model Number	Hose Capacity of Reel feet m					Approx. Weight Crank Rewind lb. kg		Reel Dimensions*** in. mm						
	I.D. in. mm	Round Hose		Collapsible Hose		NET	SHIP	A	B	E	F	G	H	X
		1	1-1/2	1-1/2	1-3/4									
		25	38	38	44									
O.D. in. mm	1-9/16	2-1/16	3/4 x 3	7/8 x 3-1/4										
	mm	40	52	19 x 76	22 x 83									
3516-25-26	50	–	50	50	95	130	13	7.5	24.75	26	27.88	15.5	7.75	
	15	–	15	15	43	59	330	191	629	660	708	394	197	
3520-25-26	100	50	100	75	104	139	17	11.5	24.75	30	27.88	15.5	9	
	30	15	30	23	47	63	432	292	629	762	708	394	229	
3524-25-26	150	75	150	100	113	157	21	15.5	24.75	34	27.88	15.5	13	
	46	23	46	30	51	71	533	394	629	864	708	394	330	
3528-25-26	200	100	200	150	123	173	25.5	20	24.75	38.5	27.88	15.5	17.5	
	61	30	61	46	56	78	648	508	629	978	708	394	445	
3524-30-31	200	100	250	150	124	174	21	15.5	28.75	34	29.88	15.5	13	
	61	30	76	46	56	79	533	394	730	864	759	394	330	
3528-30-31	250	150	300	250	134	184	25.5	20	28.75	38.5	29.88	15.5	17.5	
	76	46	91	76	61	83	648	508	730	978	759	394	445	
3534-30-31	350	200	450	350	147	197	31.5	26	28.75	44.5	29.88	15.5	23.5	
	107	61	137	107	67	89	800	660	730	1130	759	394	597	
3530-33-34	400	250	450	350	138	188	27.5	22	31.75	40.5	32.38	16.5	19.5	
	122	76	137	107	63	85	699	559	806	1029	822	419	495	

Notes:

- Specifications subject to change.
- Upon request, reels can be supplied with drum lengths other than shown and with disc sizes in other diameters.
- Power rewind NOT available on these models.
- Dimension "F" is the overall length of standard model reels. For crank rewind models, 3-1/2" clearance is required to remove crank.
- Subtract 5" from "F" dimension for disc rewind models.
- Finish:** Call factory for offshore/marine finish, available at extra cost. Refer to page 3.
- Be sure to check dimensions and weights prior to ordering.**

NOTICE: A flexible connector must be used between the inlet pipe and the inlet swivel joint.

*** X, Y indicate mounting holes. See page 5.

