



- Oil-Fired
- 120V
- Stainless Steel Coil Skin
- Flat-Free Tires for Easy Handling

555HE NOW COMES WITH AUTO START/STOP STANDARD!

500 SERIES & 680SS

DIRECT DRIVE

The 500 Series delivers rugged, yet affordable, cleaning performance for a broad range of applications. The new 555HE is the most efficient hot water pressure washer in our line. It features a technologically advanced heat exchanger that takes water to higher temperatures much faster, saving time and money. All models are ETL safety certified and feature the Hotsy pump backed by a full 7-year limited warranty. All models come equipped with a 50' high-pressure hose, lance, nozzles and trigger gun.



Model 555HE



MODEL	PART NO.	GPM	PSI	HP	VOLT/PH	AMPS	FUEL	BTU/HR	PUMP MODEL	PORTABILITY	DIMENSIONS (LXWXH)	SHIP WT (LBS)
555HE	1.109-137.0	2.2	1300	2	120/1	20	Oil	185,000	Triplex - HE2126S	Std	42"x29"x42"	385
555SS	1.109-033.0	2.2	1300	2	115/1	20	Oil	214,300	Duplex - HHC165L.1	Std	33"x27"x41.5"	400
560SS	1.109-034.0	2.1	1500	2.3	115/1	20	Oil	214,300	Triplex HF2030SL	Std	33"x26"x44"	405
680SS	1.109-035.0	3	1000	2	115/1	20	Oil	289,900	Triplex - HF2830S	Std	33"x27"x45.5"	440

HE = High Efficiency SS = Stainless Steel

BUY MORE. SAVE!

Buy 5 or more 555HEs or 555SSs and save!

3 = 2% OFF, 5 = 3% OFF, 10 = 5% OFF

OPTIONS	
PART NO.	DESCRIPTION
8.717-764.0	8" Oil-Fired Vent Regulator
8.929-192.0	Float Tank (555HE Only)
8.750-486.0	360° Pivot Reel, 100'
8.903-050.0	100' 3/8" Hose Reel Kit (555SS Only)
8.929-363.0	Exhaust Adapter* (555HE Only)

OPTIONS	
PART NO.	DESCRIPTION
9.804-624.0	QC Nozzle 3.75, 15° (Yellow) (555HE Only)
9.804-625.0	QC Nozzle 3.75, 25° (Green) (555HE Only)
9.804-626.0	QC Nozzle 3.75, 40° (White) (555HE Only)
8.903-034.0	Float Tank Kit (555SS Only)

▶ Field Installed ▶ Factory Installed

* NOTE: Must be ordered if the vent regulator [8.717-764.0] is used or the machine is connected to an exhaust stack



Model 680SS



Model 555SS