

- NG- or LP-Fired
- 115V/1PH or 230V/1 PH
- Hotsy Direct-Drive Pump
- Flat-Free Tires for Easy Handling

## LP/NG SERIES

## DIRECT DRIVE

These hot water washers are heated with either LP or NG, and offer cleaning power up to 1500 PSI. All models are ETL safety certified and feature the Hotsy pump backed by a full 7-year limited warranty. All models come equipped with a 50' high-pressure hose, lance, nozzles and trigger gun.





Model 558-Propane (shown with optional Portagear & propane tank)







MODEL	PART NO.	GPM	PSI	НР	VOLT/ PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DRIVE	DIMENSIONS (LXWXH)	SHIP WT (LBS)	
558	1.109-610.0	2.2	1300	2	115/1	18	LP	214,300	Duplex - HHC165L.1	Direct	31.5"x26"x41"	350	

MODEL	PART NO.	GPM	PSI	НР	VOLT/ PH	AMPS	FUEL	BTU/HR	PUMP MODEL	DRIVE	DIMENSIONS (LXWXH)	SHIP WT (LBS)	
771	1.109-611.0	3.0	1500	3	230/1	13	LP	280,000	HF2830S	Direct	32"x27"x45.5"	415	
772	1.109-037.0	3.0	1500	3	230/1	13	NG	338,000	HF2830S	Direct	32"x27"x45.5"	415	

Portability is optional on these models unless ordered with the portagear kit PN 8.903-049.0.

OPTIONS		
PART NO.	DESCRIPTION	
8.717-728.0	8" LP Gas-Fired Draft Diverter	Þ
8.903-049.0	Portagear	
8.717-791.0	Propane Tank, 43 lb. (Model 558 & 771)	Þ

▶ Field Installed ▶ Factory Installed

See PAGE 34 for other configured options thru the SPECIALS DEPARTMENT.