- Natural Gas, Oil or optional LP-Fired
- Remote-ready
- Hotsy Belt Drive Pump
- Stainless Steel Coil Skin

Smart Relay Control provides control over run time, auto start/stop and shut down

functionality

DRIVE

The 1800 Series provides stationary cleaning with hot water indoors. The 7 models are electric-powered and natural gas, oil or optional LP gasheated. The coil skin comes standard with stainless steel. The sleek cabinet has removable side and front panels, making it easy for routine scheduled maintenance and service. The Smart Relay allows the washer to be customized to individual needs, and is protected behind the front panel. All models are ETL safety certified and feature the Hotsy pump backed by a full 7-year limited warranty. All models come equipped with a 50' high-pressure hose, lance, nozzles and trigger gun.









MODEL	PART NO.	GPM	PSI	НР	VOLT/ PH	AMPS	FUEL	BTU/HR	PUMP Model	DIMENSIONS (LXWXH)	SHIP WT (LBS)
1812SS	1.109-660.0	6.0	2500	10	230/1	42	NG	558,050	HX9536L.2	51"x31"x53.25"	1,020
1830SS	1.109-665.0	6.0	3000	15	230/3	40	0il*	579,776	HX9536L.2	51"x31"x53.25"	1,020
1832SS	1.109-662.0	6.0	3000	15	230/3	38	NG	558,050	HX9536L.2	51"x31"x53.25"	1,020
1832SS-208	1.109-661.0	6.0	3000	15	208/3	41	NG	558,050	HX9536L.2	51"x31"x53.25"	1,020
1833SS	1.109-666.0	6.0	3000	15	460/3	21	0il*	579,776	HX9536L.2	51"x31"x53.25"	1,020
1835SS	1.109-663.0	6.0	3000	15	460/3	19	NG	558,050	HX9536L.2	51"x31"x53.25"	1,020
1836SS	1.109-664.0	6.0	3000	15	575/3	16	NG	558,050	HX9536L.2	51"x31"x53.25"	1,020

^{*}Oil-fired models are not supplied with a fuel tank

OPTIONS		
PART NO.	DESCRIPTION	
8.916-989.0	Remote Station (image 1 below)	•
8.916-988.0	Soap Solenoid and Switch	
8.749-806.0	10" Power Dampener	•
8.749-807.0	Power Dampener Wiring Harness	
9.801-040.0	10" Natural Gas- or LP Gas-Fired Draft Diverter	•

1				
of	0		19	
	7			
of		TO S		
	E			

thru the SPECIALS DEPARTMENT.





Mile)		•
PAGE 34 for otl	her configured options	

OPTIONS		
PART NO.	DESCRIPTION	LIST PRICE
9.803-452.0	Water Inlet Solenoid	•
8.924-814.0	R-Con Wireless Remote Kit (1 remote /1 receiver) (image 2 below)	•
8.925-072.0	R-Con Wireless Remote Kit (2 remotes/1 receiver)	•
8.924-878.0	Wall Mount Remote Bracket for R-Con (image 3 below)	•
8.756-329.0°	Replacement Remote (transmitter only)	•
8.903-074.0	LP Conversion Kit	•

- ▶ Field Installed ▶ Factory Installed
- Please Note: R-Con Wireless Remote comes from vendor, is custom made to order and is not universal. When ordering, please contact customer service to supply the serial number off the transmitter you have along with the channel number, so we can pass along that information to the vendor.